

SECTION 236213 - PACKAGED AIR-COOLED REFRIGERANT COMPRESSOR AND CONDENSER UNITS

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Condensing unit package.
- B. Charge of refrigerant and oil.
- C. Controls and control connections.
- D. Refrigerant piping connections.
- E. Electrical power connections.

1.2 RELATED REQUIREMENTS

- A. Section 033000 - Cast-in-Place Concrete: Concrete bases.
- B. Section 230513 - Common Motor Requirements for HVAC Equipment.
- C. Section 230548 - Vibration and Seismic Controls for HVAC Piping and Equipment: Placement of vibration isolators.
- D. Section 232300 - Refrigerant Piping.
- E. Section 235400 - Furnaces.
- F. Section 238216 - Air Coils.
- G. Section 230993 - Sequence of Operations for HVAC Controls.
- H. Section 262717 - Equipment Wiring: Electrical characteristics and wiring connections.

1.3 REFERENCE STANDARDS

- A. ARI 210/240 - Standard for Performance Rating of Unitary Air Conditioning and Air-Source Heat Pump Equipment; Air-Conditioning, Heating, and Refrigeration Institute; 2008.
- B. ARI 365 - Commercial and Industrial Unitary Air-Conditioning Condensing Units; Air-Conditioning, Heating, and Refrigeration Institute; 2009.
- C. ASHRAE Std 15 - Safety Standard for Refrigeration Systems; American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc.; 2007.

- D. ASHRAE Std 23 - Methods of Testing for Rating Positive Displacement Refrigerant Compressors and Condensing Units; American Society of heating, Refrigerating and Air-Conditioning Engineers, Inc.; 2005.
- E. ASHRAE Std 90.1 - Energy Efficient Design of New Buildings Except Low-Rise Residential Buildings; American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc.; 2007.
- F. NEMA 250 - Enclosures for Electrical Equipment (1000 Volts Maximum); National Electrical Manufacturers Association; 2008.
- G. NEMA MG 1 - Motors and Generators; National Electrical Manufacturers Association; 2007.
- H. UL 207 - Refrigerant-Containing Components and Accessories, Nonelectrical; Underwriters Laboratories Inc.; Current Edition, Including All Revisions.

1.4 PERFORMANCE REQUIREMENTS:SEE SCHEDULE ON PLANS.

1.5 SUBMITTALS

- A. See Section 013300 - Submittal Procedures, for submittal procedures.
- B. Product Data: Provide rated capacities, weights specialties and accessories, electrical nameplate data, and wiring diagrams. Include equipment served by condensing units in submittal, or submit at same time, to ensure capacities are complementary.
- C. Shop Drawings: Indicate components, assembly, dimensions, weights and loadings, required clearances, and location and size of field connections. Include schematic layouts showing condensing units, cooling coils, refrigerant piping, and accessories required for complete system.
- D. Design Data: Indicate pipe and equipment sizing.
- E. Manufacturer's Instructions: Submit manufacturer's complete installation instructions.
- F. Operation and Maintenance Data: Include start-up instructions, maintenance instructions, parts lists, controls, and accessories.
- G. Warranty: Submit manufacturer's warranty and ensure forms have been filled out in Owner's name and registered with manufacturer.
- H. Maintenance Materials: Furnish the following for Owner's use in maintenance of project.
 - 1. See Section 016000 - Product Requirements, for additional provisions.

1.6 QUALITY ASSURANCE

- A. Products Requiring Electrical Connection: Listed and classified by Underwriters

Laboratories Inc. as suitable for the purpose specified and indicated.

1.7 DELIVERY, STORAGE, AND HANDLING

- A. Comply with manufacturer's installation instructions for rigging, unloading, and transporting units.

1.8 WARRANTY

- A. See Section 017700 - Closeout Procedures, for additional warranty requirements.
- B. Provide a five year warranty to include coverage for refrigerant compressors.

PART 2 PRODUCTS

2.1 MANUFACTURERS

- A. Carrier Corporation: www.carrier.com.
- B. Trane Inc: www.trane.com.
- C. YORK: www.york.com.
- D. Substitutions: See Section 016000 - Product Requirements.

2.2 MANUFACTURED UNITS

- A. Units: Self-contained, packaged, factory assembled and pre-wired units suitable for outdoor use consisting of cabinet, compressors, condensing coil and fans, integral sub-cooling coil, controls, liquid receiver, wind deflector, and screens.
- B. Construction and Ratings: In accordance with ARI 210/240. Testing shall be in accordance with ASHRAE Std 23.
- C. Performance Ratings: Energy Efficiency Rating (EER) and Coefficient of Performance (COP) not less than prescribed by ASHRAE Std 90.1.

2.3 CASING

- A. House components in welded steel frame with galvanized steel panels with weather resistant, baked enamel finish.
- B. Provide removable access doors or panels with quick fasteners and piano hinges.

2.4 CONDENSER COILS

- A. Coils: Aluminum fins mechanically bonded to seamless copper tubing. Provide sub-cooling

circuits. Air test under water to 425 psig (2900 kPa), and vacuum dehydrate. Seal with holding charge of nitrogen.

- B. Coil Guard: Expanded metal with lint screens.

2.5 FANS AND MOTORS

- A. Vertical discharge direct driven propeller type condenser fans with fan guard on discharge. Equip with roller or ball bearings with grease fittings extended to outside of casing.
- B. Weatherproof motors suitable for outdoor use, single phase permanent split capacitor or 3 phase, with permanent lubricated ball bearings and built in current and thermal overload protection. Refer to Section 230513.

2.6 COMPRESSORS

- A. Compressor: Hermetic scroll type.
- B. Mounting: Statically and dynamically balance rotating parts and mount on rubber-in-shear vibration isolators. Internally isolate hermetic units on springs. Refer to Section 230548.
- C. Lubrication System: Reversible, positive displacement oil pump with oil charging valve, oil level sight glass, and magnetic plug or strainer.
- D. Motor: Constant speed 1800 rpm suction gas cooled with electronic sensor and winding over temperature protection, designed for across-the-line starting. Refer to Section 230513. Furnish with starter.

2.7 REFRIGERANT CIRCUIT

- A. Provide each unit with one refrigerant circuit, factory supplied and piped. Refer to Section 232300.
- B. For each refrigerant circuit, provide:
 1. Filter dryer replaceable core type.
 2. Liquid line sight glass and moisture indicator.
 3. Thermal expansion valve for maximum operating pressure.
 4. Insulated suction line.
 5. Suction and liquid line service valves and gage ports.
 6. Liquid line solenoid valve.
 7. Charging valve.
 8. Discharge line check valve.
 9. Compressor discharge service valve.

10. Condenser pressure relief valve.

2.8 CONTROLS

- A. On unit, mount weatherproof steel control panel, NEMA 250, containing power and control wiring, molded case disconnect switch, factory wired with single point power connection. Factory mount disconnect switch on unit under provisions of Section 262717.
- B. Provide safety controls arranged so any one will shut down machine:
 - 1. High discharge pressure switch (manual reset) for each compressor.
 - 2. Low suction pressure switch (automatic reset) for each compressor.
 - 3. Oil Pressure switch (manual reset).
- C. Provide the following operating controls:
 - 1. Refer to Section 230993.
 - 2. Thermostat located in room cycles compressors activates cylinder unloaders.
 - 3. One minute off timer prevents compressor from short cycling.
 - 4. Periodic pump-out timer to pump down on high evaporator refrigerant pressure.
 - 5. Low ambient temperature controls.
 - 6. Lead-lag switch to alternate compressor operation.
- D. Provide controls to permit operation down to 0 degrees F (-18 degrees C) ambient temperature.
 - 1. Thermostat to cycle fan motors in response to outdoor ambient temperature.
 - 2. Head pressure switch to cycle fan motors in response to refrigerant condensing pressure.
 - 3. Solid state control to vary speed of one condenser fan motor in response to refrigerant condensing pressure.
 - 4. Electronic control consisting of mixing damper assembly, controlled to maintain constant refrigerant condensing pressure.
- E. Gages: Prepiped for suction and discharge refrigerant pressures and oil pressure for each compressor.
- F. Provide electric solid state microcomputer based room thermostat, located as indicated.
 - 1. Incorporate:
 - a. Automatic switching from heating to cooling.
 - b. Preferential rate control to minimize overshoot and deviation from set point.
 - c. Set-up for four separate temperatures per day.
 - d. Instant override of setpoint for continuous or timed period from one hour to 31 days.
 - e. Short cycle protection.
 - f. Programming based on weekdays, Saturday and Sunday.

- g. Switch selection features including imperial or metric display, 12 or 24 hour clock, keyboard disable, remote sensor, fan on-auto.
- 2. Display shall include:
 - a. Time of Day.
 - b. Actual room temperature.
 - c. Programmed temperature.
 - d. Programmed time.
 - e. Duration of timed override.
 - f. Day of week.
 - g. System mode indication: Heating, cooling, auto, off, fan auto, fan on.
 - h. Stage (heating or cooling) operation.

PART 3 EXECUTION

3.1 INSTALLATION

- A. Install in accordance with manufacturer's installation instructions.
- B. Complete structural, mechanical, and electrical connections in accordance with manufacturer's installation instructions.
- C. Install units on vibration isolation. Refer to Section 230548.
- D. Provide connection to refrigeration piping system and evaporators. Refer to Section 232300. Comply with ASHRAE Std 15.

3.2 SYSTEM STARTUP

- A. Supply initial charge of refrigerant and oil for each refrigeration system. Replace losses of oil or refrigerant prior to end of correction period.
- B. Charge system with refrigerant and test entire system for leaks after completion of installation. Repair leaks, put system into operation, and test equipment performance.
- C. Shut-down system if initial start-up and testing takes place in winter and machines are to remain inoperative. Repeat start-up and testing operation at beginning of first cooling season.
- D. Provide cooling season start-up, and winter season shut-down for first year of operation.

END OF SECTION